

Panasonic **LED Lighting** Solutions

The real challenger light





LED Splashproof

NNFC4033154 - NNFC4038154

220-240V AC, Ceiling Type 36W LED Splashproof

Challenging design creates protection, durability, and continuous light with its smooth appearance.


Panasonic LED Splashproof's attractive, neutral and aesthetic design makes it suitable for applications both in commercial, industrial and the residential projects. It's lightweight design allows quick and easy installation into projects. It's long life and high lumen output provides energy-efficiency and low-maintenance. It is also a good alternative to traditional fluorescent waterproof fixtures.

Product benefits:

- High luminous efficacy up to
- 110 lm/wSuperior life span with 25000hr.
- Reduced replacement and
- maintenance costsAmazing optical diffuzer with high transmittion
- Areas of application:

• Residential

- Industrial
 - Commercial



TECHNICAL SPECIFICATIONS

	NNFC4033154	NNFC4038154
Model Name	LED Splash Proof Light	LED Splash Proof Light
	36W 3960lm 840 25Khr	36W 3960lm 865 25Khr
Tolerance Voltage Range	220-240 V AC	220-240 V AC
Input Frequency	50/60Hz	50/60Hz
Power Consumption (Typical)	36W	36W
Lumen	3960 lm	3960 lm
CCT (Correlated Color Temp.)	4000 K	6500 K
Life	25000 h	25000 h
CRI (Color Rendering Index)	Ra80	Ra80
Energy Label (New)	E	E
Standard Deviation of Color Matching	≤6	≤6
Startup Time	<0.5S	<0.5S
IP Rating	IP 65	IP 65
Operating Temperature Range	+5 / +35 °C	+5 / +35 °C
Storage Temperature Range	-20 / +60 °C	-20 / +60 °C
Fixture Dimension	1212*70.5*50.6 mm	1212*70.5*50.6 mm
Product Material	Poly Carbon (PC)	Poly Carbon (PC)
Diffuser Material	Poly Carbon (PC)	Poly Carbon (PC)
Connector Type	Non	Non
Dimming Option	No	No
Certificates	CE, ERP, RoHS	CE, ERP, RoHS
Total Weight	1.0 Kg	1.0 Kg
Pack Qty	20	20







25.000 Hours





Class

s CRI

